




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ³ : G09G 1/00	A1	(11) International Publication Number: WO 84/ 02025 (43) International Publication Date: 24 May 1984 (24.05.84)
<p>(21) International Application Number: PCT/US83/01790</p> <p>(22) International Filing Date: 14 November 1983 (14.11.83)</p> <p>(31) Priority Application Number: 442,544</p> <p>(32) Priority Date: 18 November 1982 (18.11.82)</p> <p>(33) Priority Country: US</p> <p>(71)(72) Applicant and Inventor: GREENBLATT, Richard, W. [US/US]; 19 Mary Beth Drive, Suffern, NY 10901 (US).</p> <p>(74) Agent: HUNTER, Edward, B.; Nolte and Nolte, 350 Jericho Turnpike, Jericho, NY 11753 (US).</p> <p>(81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), FR (European patent), GB (European patent), JP, LU (European patent), NL (European patent), SE (European patent).</p>		<p>Published With international search report. With amended claims.</p>

(54) Title: PORTABLE INFORMATION DISPLAY

(57) Abstract

A portable information display system is for connection to a remote computer. The system avoids the bulky computer 'terminals' of the prior art by eliminating the disc drives and other external memory devices. The entire unit fits into a housing (18) which is sized to fit under a standard airline seat. Component features include a modem (52), power supply (54), keyboard (15), CRT display (28), and protocol converter (50) arranged to provide optimal operation in a limited space.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	LI	Liechtenstein
AU	Australia	LK	Sri Lanka
BE	Belgium	LU	Luxembourg
BR	Brazil	MC	Monaco
CF	Central African Republic	MG	Madagascar
CG	Congo	MR	Mauritania
CH	Switzerland	MW	Malawi
CM	Cameroon	NL	Netherlands
DE	Germany, Federal Republic of	NO	Norway
DK	Denmark	RO	Romania
FI	Finland	SE	Sweden
FR	France	SN	Senegal
GA	Gabon	SU	Soviet Union
GB	United Kingdom	TD	Chad
HU	Hungary	TG	Togo
JP	Japan	US	United States of America
KP	Democratic People's Republic of Korea		

PORTABLE INFORMATION DISPLAYBACKGROUND OF THE INVENTION

The present invention relates to information and display systems or terminals and, specifically, relates to portable terminals having visual displays and keyboards contained within a package easily transportable by a single person.

Technological advances in the computer industry and in computer related instruments have caused the overall size of many computing systems to be decreased drastically. Indeed, the fact that the computers can be of such a small size has added much to their marketability. Along with the reduction in size of the computer has also come the proliferation of small "terminals". The overall dimensions of such small terminals have also been reduced substantially and now are generally desk-top size. These so-called "portable" terminals typically employ a cathode ray tube (CRT), a keyboard, one or more disc drives for accepting the software that permits the terminal to emulate the system with which it communicates, and a relatively small amount of local storage.

There are presently two main kinds of CRT terminals, one of which runs on or "talks to" IBM mainframe computers, such as the IBM 360/370 and 3000/4300 series. These are known as 3270 terminals. The second kind of CRT terminals run on or talk to mainframe computers or minicomputers made by other manufacturers. This second kind of terminal is generally referred to as an ASCII terminal, which is an acronym for American Standard Code for Information Interchange.

The CRT terminal is typically used in combination with the appropriate software, via the disc drive, to permit the terminal to emulate the specific host computer. This emulation is based



- 2 -

upon the particular protocol used by the computer. Integral with this protocol compatibility is the data communication methodology that is employed. The original data communications protocol used by the 3270 terminals is known as binary synchronous communications (BSC) or bisynch. A more recent IBM data communications methodology is known as Systems Network Architecture/Synchronous Data Link Control (SNA/SDLC). Therefore, the terminal selected by the user must be compatible with the data communication methodology of the main computer. In that regard, there are now available devices known as "protocol convertors" to meet either the bisynch or SNA/SDLC standard. Thus, many present terminals are actually user-programmed microcomputers requiring a controller to meet the various protocols.

The trend then in this kind of computer support equipment is toward more and more compatibility in these terminals and, along with this, go increases in system complexity, cost and size. While being loosely referred to as "portable", these presently available terminals have gotten heavier and more difficult to transport and, in all events, are not portable in the sense that they may be easily transported from one location to another by a single person; e.g., by public transportation, such as being placed under an airline seat.

SUMMARY OF THE INVENTION

The present invention teaches a completely portable information display system that corresponds generally to a computer "terminal" but involves a compact embodiment of a size to fit under a typical airline seat. The preferred embodiment involves a 3270 interactive bisynchronous device. The invention employs subassemblies, such as a modem, a power supply, a cathode ray tube display, a main circuit board or convertor, and a keyboard specially arranged within a housing of a size and configuration for portable use. Because the present invention is intended to be an information display system, disc drives are eliminated in the



- 3 -

present construction and no software emulation is intended. Nevertheless, through the use of internal firmware the present invention is capable of operating under various protocols; e.g., bisynch and SNA/SDLC. The invention is intended for connection through conventional voice-grade telephone lines to a computing facility and employs an on-board modem within the housing. The preferred embodiment also provides a video output signal, as well as a printer output signal, to drive different displays or hard-copy printers.

The invention is made up of "off the shelf" subassemblies chosen in such a way that no performance benefits are sacrificed, yet all of these subassemblies can be optimally arranged within a small housing with a resultant low overall weight.

The arrangement of the various subassemblies employed in the present invention inside the portable-sized housing is such to preclude any heat or insulation problems, which would ultimately degrade performance, as well as to minimize internal inductance and EMI problems.

Accordingly, it is an object of the present invention to provide a portable 3270 information display system for communicating with a main computer via voice-grade telephone lines, employing off-the-shelf subassemblies, including an internal modem, and being arranged in a housing of a size/weight configuration suitable for portable use.

The manner in which this and other objects are accomplished by the present invention will be seen in the following description.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective of the inventive unit showing the display tube, the keyboard, and external connections;



- 4 -

Fig. 2 is a perspective of the inventive unit showing the inside thereof in partial schematic form; and

Fig. 3 is a block diagram showing the functional sub-assemblies of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to Fig. 1, the inventive assembly 10 is shown opened up, so as to place the unit in an operable position. Specifically, the keyboard assembly, shown generally at 12, comprises a standard key pad section 15 contained within a metal housing or shell 16 that forms the lid of the unit 10. The lid 16 is hingedly affixed to the main housing 18 of the unit via two hinges 20, 22 and can be fastened to the outer housing 18 by luggage-type clips 24, 26. The main functional elements of the present invention, which will be discussed in detail hereinbelow, are mounted inside housing 18. A conventional carrying handle (not shown) may be affixed to the center of lid 16.

The front of the unit 10 includes a cathode ray tube 28 that provides the visual display to the operator. The conventional CRT controls are shown typically at 30. A standard coaxial cable jack 32 provides video output signals for use at a remote or auxiliary display. Also, on the front of the unit is the standard on/off switch 34, as well as line current overload protection in the form of a fuse 36. An auxiliary output jack 38, shown as a standard D-type connector, provides a means for electrical connection to a printer (not shown), thereby permitting the present invention to provide a hard-copy print out, as well as the visual display on the cathode ray tube 28. A modular phone jack 40 connects the modular plug of a voice-grade touch-tone phone line to the modem of the inventive unit. A twelve key touch tone panel 42 and on/off switch 44 are arranged on the front of the unit. This phone key panel permits phone line dialing once the unit is connected to the computer via the modem. This key

panel 42 may not always be required and, if not, a jack may be provided for connection of a push button handset having an on/off switch. The power cord 45 enters the unit at the front panel, so that once the lid 16 is closed and fastened to the housing 18, nothing protrudes from the unit. The keyboard assembly 12 is connected to the electronics of the main unit by a flexible ribbon cable 46.

In Fig. 2, the functional subassemblies of the invention are shown arranged inside the metal housing 18 that is of a size and configuration for portable use. The front control panel has been removed in the view of Fig. 2 to show the interior arrangement of these subassemblies.

The present invention teaches a display terminal that specifically must be portable and, therefore, teaches the avoidance of the software emulation approach. This then permits the elimination of all the hardware and electronics that are required by a disc drive. The present invention requires only certain subassemblies; e.g., the cathode ray tube 28, a main circuit board 50 or convertor that provides the necessary protocol conversions to permit 3270 data communications, a modem 52, and a power supply 54 that includes a power transformer 56. By carefully choosing these subassemblies, and by eliminating the disc drive needed for software emulation, the invention teaches the arrangement of all necessary subassemblies inside a rigid housing 18 of a size to permit easy, single handed portability.

The video signal available at jack 32 on the front panel is fed to the jack by line 58 from the CRT 24. The printer connection available at jack 38 on the front panel is fed thereto by ribbon cable 60 that originates on the main circuit board 50, also termed the convertor. The ribbon cable 46 used to connect the keyboard unit 12 with the main unit emanates from the main circuit board 50. The connection to the voice-grade dial line is fed through the modular plug 32 to the modem 52 by line 62. The main circuit board 50 includes circuitry to accomplish the

- 6 -

protocol data communication conversions, as well as the digital logic necessary to convert the information provided into a format for display on the CRT and to convert the keyboard information to display information. The main circuit board 50 is available from several sources, such as Local Data of Torrance, California and Term-Tronics of Alexandria, Virginia. The power supply 54 is arranged against the rear wall of the housing and operates in conjunction with the power transformer 56 also affixed to the rear wall. The line current, as provided by the power cord 45, is fed to the transformer on line 64. The power supply 54 is connected to provide regulated voltages to the CRT 24 and the main circuit board 50, on lines 66 and 68, respectively.

Fig. 3 shows the electrical interconnections between the basic functional elements of the present invention and, specifically, shows the mainframe computer 80 located at some remote site and interconnected with the present invention, as represented within dashed line 82, via voice-grade telephone lines 84. The telephone line 84 is connected to the modem 52 that is preferably selected to operate at between 110-96,000 Baud and is currently available from several manufacturers. The modem 52 is connected via multi-lines 88 to the main circuit board 50, which is itself connected via ribbon cable 46 to the keyboard 12. The cathode ray tube 28 is connected to the main circuit board 90 via multi-lines 94. The power supply 54 provides the proper voltages for both the cathode ray tube 28 on line 100 and the convertor 50 on line 102. The video out signal is fed out from the CRT 28 on line 58 and the printer drive signals are obtained from the main circuit board on multi-lines 60. Preferably, a small fan 104 is mounted in a side wall of housing 18 to cool all the subassemblies. The fan 104 is connected to be powered by the power supply 54.

It is understood that the foregoing is presented by way of example only and is not intended to limit the present invention, except in the appended claims.



- 7 -

WHAT I CLAIM IS:

1. A self contained, lightweight, portable information display unit for providing communication with a remote computer employing a known data communication protocol, over a voice grade telephone line, consisting of:

a housing of a size and configuration for single-handed portability;

a data communications convertor arranged within said housing for converting signals into the protocol of the remote computer;

a video screen display means arranged within said housing with the screen thereof arranged for displaying information and being electrically connected to said convertor;

a manual keyboard attached to said housing and electrically connected to said convertor for providing input signals thereto;

a modem arranged within said housing and connected between the telephone lines and said convertor for modulating/demodulating signals fed to/from the computer; and

power supply means arranged within said housing and electrically connected to said display means and said convertor and with an external source of power for providing predetermined levels of power to said display means and to said convertor means.

2. The unit of Claim 1, wherein said manual keyboard means comprises a manual typewriter portion and a standard numerical keypad portion.



- 8 -

3. The unit of Claim 1, wherein said manual keyboard means is arranged within an element formed as a lid for said housing and hingedly attached thereto.

4. The unit of Claim 1, wherein said modulator/demodulator is connected to said phone line by a modular phone plug means.

5. The unit of Claim 1, further comprising a ventilating fan arranged in said housing and connected to said power supply for providing air circulation within the interior of said housing.

6. Information display apparatus for use with a computer, consisting of:

a housing of a size and configuration for personal portability;

data communications convertor means arranged within said housing for converting, respectively, input or output signals to or from a communications protocol employed by the computer;

modulator/demodular means arranged within said housing and connected to said convertor for modulating or demodulating signals from the computer;

means for connecting voice grade phone lines, carrying signals from the computer, to said modulator/demodulator means;

cathode ray tube display means arranged within said housing and connected to be driven by said convertor means;

manual keyboard means attached to said housing for providing input signals to said convertor means; and

power supply means arranged within said housing and electrically connected with an external source of power for providing



selected power levels to said display means and said convertor means.

7. The apparatus of Claim 6, wherein said manual keyboard means comprises a manual typewriter portion and a standard numerical keypad portion.

8. The apparatus of Claim 6, wherein said manual keyboard means is arranged within apparatus formed as a lid for said housing and hingedly attached thereto.

9. The apparatus for Claim 6, wherein said means for connecting voice grade phone lines carrying signals from the computer to said modulator/demodulator means comprises a modular phone plug means.

10. The apparatus of Claim 6, further comprising a ventilating fan arranged in said housing and connected to said power supply for providing air circulation within the interior of said housing.



4
AMENDED CLAIMS

[received by the International Bureau on 16 April 1984 (16.04.84) ;
original claims 1 to 10 have been replaced by new claims 1 to 4]

1. A self contained, lightweight, portable information display unit, without software and disc drive means, for providing communication only with a remote computer, employing a known bisynchronous 3270 data communication protocol, over a voice grade telephone line, consisting only of:

a housing having two compartments connected by hinge means for pivoting said compartments to relative open and closed positions and including hand carrying means secured to a top portion of one of said compartments and being of a size and configuration for single-handed portability via said hand carrying means;

a data communications converter arranged within one of said housing compartments for converting signals only into the bisynchronous 3270 data protocol of the remote computer;

cathode ray tube display means arranged within said one of said housing compartments with the screen thereof arranged for displaying information when said compartments are in the open position and being electrically connected to said converter;

a manual keyboard arranged within the other of said housing compartments and electrically connected to said converter for providing input signals thereto, said keyboard facing said cathode ray tube display means when said compartments are in the closed position and positioned for use by an operator when said compartments are in the open position;

a modem arranged within said one of said housing compartments for modulating/demodulating signals fed to and from the remote computer;



a modular phone line connector mounted on said one of said housing compartments and connecting said modem and providing an external connection between said modem and telephone lines for sending signals to and receiving signals from the remote computer;

power supply means arranged within said one of said housing compartments and electrically connected to said display means and said converter and with an external source of power for providing predetermined levels of power to said display means and to said converter means;

said manual keyboard comprising a manual typewriter portion and a standard numerical keypad portion; and

a ventilating fan is arranged in said housing and connected to said power supply for providing air circulation within the interior of said housing.

2. The unit of Claim 1, wherein said modular phone line connector is a jack connection for a modular phone plug.

3. The unit of Claim 2, further consisting of a second jack connection mounted on said one of said housing compartments and connecting said converter and providing an external connection between said converter and a printer.

4. The unit of Claim 3 further consisting of a coaxial cable jack connection is mounted on said one of said housing compartments and connecting said cathode ray tube and providing an external connection for a remote display means.

1/3





FIG. 1

SUBSTITUTE SHEET





3/3




FIG. 3

INTERNATIONAL SEARCH REPORT PCT/US83/01790

International Application No

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ³ According to International Patent Classification (IPC) or to both National Classification and IPC INT. CL. ³ G09 G 1/00 U.S. CL. 340/711, 700																				
II. FIELDS SEARCHED <div style="text-align: right; font-size: small;">Minimum Documentation Searched ⁴</div> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%; border-bottom: 1px solid black; vertical-align: top;"> Classification System US </td> <td style="border-bottom: 1px solid black; vertical-align: top;"> Classification Symbols 340/700, 711, 712, 720, 365R, 365S; 179/2DP, 2C, LEXIS LEXPAT MS SEARCH FOR 364/200, 900 </td> </tr> </table> <div style="font-size: x-small; text-align: center;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are included in the Fields Searched ⁵</div>			Classification System US	Classification Symbols 340/700, 711, 712, 720, 365R, 365S; 179/2DP, 2C, LEXIS LEXPAT MS SEARCH FOR 364/200, 900																
Classification System US	Classification Symbols 340/700, 711, 712, 720, 365R, 365S; 179/2DP, 2C, LEXIS LEXPAT MS SEARCH FOR 364/200, 900																			
III. DOCUMENTS CONSIDERED TO BE RELEVANT ^{1,4} <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; border-bottom: 1px solid black; font-size: x-small;">Category ²</th> <th style="width: 70%; border-bottom: 1px solid black; font-size: x-small;">Citation of Document, ^{1,6} with indication, where appropriate, of the relevant passages ^{1,7}</th> <th style="width: 20%; border-bottom: 1px solid black; font-size: x-small;">Relevant to Claim No. ^{1,8}</th> </tr> <tr> <td style="vertical-align: top;">A</td> <td>US, A, 4,007,443, (Bromberg et al), 08 February 1977</td> <td style="vertical-align: top;">1-10</td> </tr> <tr> <td style="vertical-align: top;">A</td> <td>US, A, 4,258,387, (Lemelson et al), 24 March 1981</td> <td style="vertical-align: top;">1-10</td> </tr> <tr> <td style="vertical-align: top;">X</td> <td>US, A, 4,268,721, (Nielson et al), 19 May 1981</td> <td style="vertical-align: top;">1-3, 5-8</td> </tr> <tr> <td style="vertical-align: top;">A</td> <td>US, A, 4,291,198, (Anderson et al), 22 September 1981</td> <td style="vertical-align: top;">1-10</td> </tr> <tr> <td style="vertical-align: top;">A</td> <td>US, A, 4,333,097, (Buric et al), 01 June 1982</td> <td style="vertical-align: top;">1-10</td> </tr> </table>			Category ²	Citation of Document, ^{1,6} with indication, where appropriate, of the relevant passages ^{1,7}	Relevant to Claim No. ^{1,8}	A	US, A, 4,007,443, (Bromberg et al), 08 February 1977	1-10	A	US, A, 4,258,387, (Lemelson et al), 24 March 1981	1-10	X	US, A, 4,268,721, (Nielson et al), 19 May 1981	1-3, 5-8	A	US, A, 4,291,198, (Anderson et al), 22 September 1981	1-10	A	US, A, 4,333,097, (Buric et al), 01 June 1982	1-10
Category ²	Citation of Document, ^{1,6} with indication, where appropriate, of the relevant passages ^{1,7}	Relevant to Claim No. ^{1,8}																		
A	US, A, 4,007,443, (Bromberg et al), 08 February 1977	1-10																		
A	US, A, 4,258,387, (Lemelson et al), 24 March 1981	1-10																		
X	US, A, 4,268,721, (Nielson et al), 19 May 1981	1-3, 5-8																		
A	US, A, 4,291,198, (Anderson et al), 22 September 1981	1-10																		
A	US, A, 4,333,097, (Buric et al), 01 June 1982	1-10																		
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>[*] Special categories of cited documents: ^{1,5}</p> <p>^{"A"} document defining the general state of the art which is not considered to be of particular relevance</p> <p>^{"E"} earlier document but published on or after the international filing date</p> <p>^{"L"} document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>^{"O"} document referring to an oral disclosure, use, exhibition or other means</p> <p>^{"P"} document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 50%;"> <p>^{"T"} later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>^{"X"} document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>^{"Y"} document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>^{"A"} document member of the same patent family</p> </div> </div>																				
IV. CERTIFICATION <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black; vertical-align: top;"> Date of the Actual Completion of the International Search ¹ 12 January 1984 </td> <td style="width: 50%; border-bottom: 1px solid black; vertical-align: top;"> Date of Mailing of this International Search Report ¹ 27 JAN 1984 </td> </tr> <tr> <td style="border-bottom: 1px solid black; vertical-align: top;"> International Searching Authority ¹ ISA/US </td> <td style="border-bottom: 1px solid black; vertical-align: top;"> Signature of Authorized Officer ²⁰ <i>Gerald L. Brigance</i> Gerald L. Brigance </td> </tr> </table>			Date of the Actual Completion of the International Search ¹ 12 January 1984	Date of Mailing of this International Search Report ¹ 27 JAN 1984	International Searching Authority ¹ ISA/US	Signature of Authorized Officer ²⁰ <i>Gerald L. Brigance</i> Gerald L. Brigance														
Date of the Actual Completion of the International Search ¹ 12 January 1984	Date of Mailing of this International Search Report ¹ 27 JAN 1984																			
International Searching Authority ¹ ISA/US	Signature of Authorized Officer ²⁰ <i>Gerald L. Brigance</i> Gerald L. Brigance																			